

FineLeather™ Film

19 mic



Achieve the Look | FineLeather™ Film is a tactile wet film that adds the subtle appeal of faux fine-grain leather to flexible packaging and luxury labels. This earthy cowhide pattern is resistant to smudging, scuffing, and scratching. Ideal for products that will be handled on a regular basis, this wet film can be used on stand-up pouches, sealed bags, and decorative labels. Printed designs are able to show through clearly with high colour accuracy without being obscured by the pattern.

Made of biaxially oriented polypropylene (BOPP), FineLeather Film measures 19 microns thick. It has no adhesive layer, which makes it compatible with solventless or solvent-based lamination for flexible packaging and wet lamination and UV or LED curing for decorative labels.

KEY FEATURES

- Print Web Film
- Gives Packaging a Faux-Leather Look
- Scratch-Resistant Surface
- Accepts Reverse Printing
- Solventless/Solvent-Based Lamination

PRINTING METHODS


- Digital
- Flexographic

SUGGESTED PACKAGING FORMATS

- Labels
- Sachets
- Stand-Up Pouches
- Stick Packs
- Three-Sided Sealed Bags

nobelus[®]
CONSIDER IT FINISHED

Leather Surface
Polypropylene Core



--- Corona Treated

FineLeather™ Film

19 mic



| Properties | Description | Units | Value | Tolerance | Test Method / Standard |
|---------------------|-------------|--------------------|----------------------|-----------|------------------------|
| Film Type | - | - | Polypropylene (BOPP) | - | - |
| Thickness | - | µm mil ga | 19 0.75 75 | ± 5% | - |
| Weight | - | g/m ² | 13.6 | ± 5% | ASTM D792 |
| Yield | - | m ² /kg | 73.53 | ± 5% | ASTM D792 |
| Haze | - | % | 91 | ± 5% | ASTM D1003 |
| Gloss Level at 60° | - | Gloss Units | 15 | 15 -17 | - |
| Tensile Strength | MD | kg/mm ² | 9.12 | ± 5% | ASTM D882 |
| | TD | | 18.98 | | |
| Elongation at Break | MD | % | 132 | ± 5% | ASTM D882 |
| | TD | | 40 | | |

MD = Machine Direction
TD = Transverse Direction

STANDARD SIZES - UF226A

| Part Number | Description | Width (mm) | Length (m) |
|-----------------------|-------------------|------------|------------|
| UF226A.076.0325.02000 | FineLeather™ Film | 325 | 2,000 |
| UF226A.076.0330.02000 | FineLeather™ Film | 330 | 2,000 |
| UF226A.076.0755.02000 | FineLeather™ Film | 755 | 2,000 |

Core Size: 76 mm | Wind Direction: Apply Adhesive In

Sample rolls available upon request. Non-standard roll sizes can be made to order and will be subject to special pricing. Lead time for order fulfilment may be delayed.

nobelus[®]
CONSIDER IT FINISHED

NOTE: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Nobelus[®] makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.