

FineGlitter™ Film

50 mic



Make It Glamorous. FineGlitter™ Film gives luxury labels and flexible packaging a sparkling, glittery appeal to catch the attention of consumers. It reflects light depending on the viewing angle, which gives designs a sense of movement and versatility. This film is highly durable, and its shiny effect will not rub off with scratching or repeated handling. Ideal for labels, pouches, and other packaging, this finish will not interfere with the clarity of printed designs.

Made of cast polypropylene (CPP), FineGlitter Film measures 50 microns thick. This wet film includes no adhesive layer and is designed for wet lamination with UV or LED curing technology for labels and solventless, solvent-based, and water-based lamination for flexible packaging. It is compatible with reverse printing.

KEY FEATURES


- Striking Glitter Effect
- Reflective Sparkles Catch Light
- Delicate Tactile Finish
- Resistant to Scuffing
- Accepts Reverse Printing
- Cast Polypropylene Structure for Easy-Tear Applications
- Wet Film With No Adhesive

SUGGESTED PACKAGING FORMATS

- Luxury Labels
- Stand-Up Pouches

nobelus®
CONSIDER IT FINISHED

Sparkly Layer
Polypropylene Core



--- Corona Treated

FineGlitter™ Film

50 mic



Properties	Description	Units	Value	Tolerance	Test Method / Standard
Film Type	-	-	Cast Polypropylene (CPP)	-	-
Thickness	-	μm mil ga	50 2.0 200	± 5%	-
Weight	-	g/m ²	45	± 5%	Internal Method
Yield	-	m ² /kg	22	± 5%	ASTM D4321
Haze	-	%	N/A [†]	-	-
Gloss Level at 60°	-	Gloss Units	N/A [†]	-	-
Surface Energy	Finish	Dyne	46*	± 5%	ASTM D2578
	Non-Adhesive		40*		
Coefficient of Friction	-	Dynamic	-	-	ASTM 1894
		Static	-	-	
Tensile Strength	MD	PSI	-	-	ASTM D882
	TD		-		
Elongation at Break	MD	%	-	-	ASTM D882
	TD		-		

Considerations: *Corona Treated. Dyne levels may vary due to environment, handling procedures, and time elapsed since corona treatment.

[†]Not measured - not representative due to rough and angular surface design.

MD = Machine Direction

TD = Transverse Direction

STANDARD SIZES - UF256E

Part Number	Description	Width (mm)	Length (m)
UF256E.076.0325.01500	FineGlitter™ Film	325	1,500
UF256E.076.0760.01500	FineGlitter™ Film	760	1,500

Core Size: 76 mm | **Wind Direction:** Apply Adhesive In

Sample rolls available upon request. Non-standard roll sizes can be made to order and will be subject to special pricing. Lead time for order fulfilment may be delayed.

nobelus®
CONSIDER IT FINISHED

NOTE: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Nobelus® makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.